

## NEC U321Hi (Multi-Touch) Interactive Multi-Touch Projector

### Datasheet



This ultra-short throw interactive projector releases space within small to medium sized classrooms and meeting rooms, projecting onto screen sizes between 85-100" without creating shadow or glare, allowing users to get up close in comfort to interact using the Multi-Touch function.

With 1080p resolution and 10,000:1 contrast, the U321Hi Multi-Touch delivers perfect image quality for very detailed content as well as high quality movies including 3D content from Blu-Ray players, thanks to HDMI 3D support. Demanding applications in higher education such as design and engineering will appreciate the 1080p resolution for the high level of detail achieved.

### Benefits

**Great picture quality** - thanks to 1080p resolution and 10000:1 contrast.

**Almost no shadow and glare** - thanks to ultra-short throwing distance.

**Wall-mount included** - for quick and easy installation, compatible with height adjustable systems.

**Future-proof connectivity** - incl. MHL and network support.

**Cost effective replacement** - of existing NEC UM Series installations to achieve higher resolutions without re-positioning of the existing wall-mount.

## Product Information

Product Name	NEC U321Hi (Multi-Touch)
Product Group	Interactive Multi-Touch Projector
Order Code	60003945

## Image

Projection Technology	1-chip DLP™ Technology
Native Resolution	1920 x 1080 (FULL-HD)
Aspect Ratio	16:9
Contrast Ratio <sup>1</sup>	10000:1
Brightness <sup>1</sup>	3200 ANSI Lumen (approx. 85% in Eco Mode)
Lamp	260 W AC (220 W AC Eco Mode)
Light Source Life [hrs]	3000 (4000 Eco Mode)
Lens	F= 2.4, f= 3.72 mm
Lens Offset [%]	65
Projection Angle [°]	57
Projection Factor	0.25 : 1
Projection Distance [m]	0.195 - 0.306
Screen Size (diagonal) [cm] / [inch]	Maximum: 254 / 100"; Minimum: 215 / 85"
Zoom	Digital Zoom
Focus Adjustment	Manual
Supported Resolutions	1024 x 768 (XGA); 1280 x 768 (WXGA); 1440 x 900 (WXGA+); HDTV 1080i/50); 1152 x 864 (XGA); 1280 x 800 (WXGA); 1600 x 1200 (UXGA); 640 x 480 (VGA/MAC 1152 x 870 (MAC 21"); 1280 x 960 (SXGA); 1600 x 900 (WXGA++); 720 x 480 SDTV 23"); 1360 x 768 (WXGA); 1600 x 900 (WXGA++); 576p/576i; 1280 x 1024 (MAC 23"); 1366 x 768 (WXGA); 1680 x 1050 (WSXGA+); 720 x 576 SDTV 1280 x 1024 (SXGA); 1400 x 1050 (SXGA+); 480p/480i; 1280 x 720 (HDTV 720p); 1920 x 1080 (HDTV 1080i/60); 800 x 600 (SVGA); 832 x 624 (MAC 16")
Frequency	Horizontal: 15-100 kHz (RGB: 24 kHz- 100 kHz); Vertical: 50 - 120 Hz

## Connectivity

RGB (analog)	Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin
Digital	Input: 1 x HDMI™ (Deep Color, Lip sync); 1 x HDMI™ with MHL support
Video	Input: 1 x RCA
Audio	Input: 1 x 3.5 mm Stereo Mini Jack; 1 x RCA Stereo Output: 1 x 3.5 mm Stereo Mini Jack (variable)
Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN	1 x RJ45
USB	1 x Mini USB; 1 x Type A (USB 2.0 high speed)
Video Signals	NTSC; NTSC 3.58; NTSC 4.43; PAL; PAL-M; PAL-N; PAL60; SECAM

## Remote Control

Remote Control	Aspect Ratio; Audio Control; Auto Adjust; AV Mute; Digital Zoom; Direct Source Select; Freeze; Help Eco Mode; Help-function; ID set; Picture Adjust; Presentation and Mouse Control
----------------	---

## Electrical

Power Supply	100-240 V AC; 50 - 60 Hz
--------------	--------------------------

Power Consumption [W] 312 (Normal) / 264 (Eco) / 2.2 (Network Stand-by) / 0.3 (Stand-by)

---

## Mechanical

Dimensions (W x H x D) [mm] 383 x 85 x 308 (without lens and feet)

---

Weight [kg] 4.7

---

Fan Noise [dB (A)] 29 / 34 (Eco / Normal)

---

## Environmental Conditions

Operating Temperature [°C] 5 to 40

---

Operating Humidity [%] 20 to 80 non-condensing

---

Storage Temperature [°C] -20 to 60

---

Storage Humidity [%] 20 to 90 non-condensing

---

## Ergonomics

Safety and Ergonomics CE; Gost-R; RoHS; TÜV GS

---

Speakers [W] 1 x 8 (mono)

---

## Additional Features

Special Characteristics 3D ready; AMX Beacon; Auto Eco Mode; Auto Power ON/OFF; Crestron RoomView; DICOM simulation; Direct Power-Off Function; High Altitude Mode; Kensington security slot; Keypad Lock; Magnify; Manual vertical Keystone Correction (V= ±5°); NaViSet Administrator 2; Off-Timer; Optional User Logo; OSD with 30 languages; Password Security System; PJ LINK; Quick On/Off; Remote control and administration via LAN and RS232; Security Bar; Test Pattern; Wall Colour Correction

---

## Green Features

Ecological Materials 100% recyclable packaging; Downloadable manuals; ECO packaging

---

Ecological Standards ErP compliant; RoHS compliant

---

## Warranty

Projectors 3 years pan-European service

---

Light Source 6 months, max. 1000 hrs

---

## Shipping Content

Shipping Contents Attachment Plate; Interactive Module incl. 2 pens (NP04Wi); IR Remote Control (RD469E); Mini D-SUB Signal Cable (1.8 m); Multi-Touch Module (NP01TM); Power Cord; Quick Setup Guide; Security Sticker; Users Manual; Wall-mount kit NP04WK

---

## Optional Accessories

Optional Accessories DisplayNote; DLP-Link 3D Glasses (NP02GL, Volfoni-Fit); Lamp (NP34LP)

---

<sup>1</sup> Compliance with ISO21118-2012



CE



Gost-R



RoHS



TÜV GS

This document is © 2021 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 09.12.2021