

Versatile and mobile – compact and light-weight with HDMI and integrated 20W speaker.

Display content that demands attention – with XGA resolution and superb brightness levels and colour ranges, your viewers will enjoy an outstanding visual experience.

Cost effective replacement – of existing NEC M LCD model installations to achieve better imaging for lectures and presentations without wall-mount adjustment.

Product Information

Product Name	NEC ME361X
Product Group	Professional Business Projector
Order Code	60004226

Image

Projection Technology	3LCD Technology			
Native Resolution	1024 x 768 (XGA)			
Aspect Ratio	4:3			
Contrast Ratio ¹	12000:1			
Brightness ¹	3600 ANSI Lumen			
Lamp	235 W AC (140 W AC Eco Mode)			
Light Source Life [hrs]	5000 (9000 Eco Mode)			
Lens	F= 1.7-2.1, f= 17.5-29 mm			
Keystone correction	+/- 30° manual horizontal / +/- 30° manual vertical			
Projection Factor	1.3 - 2.2 : 1			
Projection Distance [m]	0.6 - 13.8			
Screen Size (diagonal) [cm] / [inch]	Maximum: 762 / 300"; Minimum: 76 / 30"			
Zoom	Manual			
Focus Adjustment	Manual			
Supported Resolutions	1024 x 768 (MAC 19"); 1024 x 768 (XGA); 1152 x 870 (MAC 21"); 1280 x 1024 (MAC 23"); 1280 x 1024 (SXGA); 1280 x 720 (HDTV 720p);	1280 x 768 (WXGA); 1280 x 800 (WXGA); 1400 x 1050 (SXGA+); 1440 x 900 (WXGA+); 1600 x 1200 (UXGA); 1600 x 900 (WXGA++);	1680 x 1050 (WSXGA+); 1920 x 1080 (HDTV 1080p/i); 1920 x 1200 (WUXGA); 640 x 480 (MAC 13"); 640 x 480 (VGA); 720 x 480 (480p);	720 x 480 (SDTV 480i); 720 x 576 (SDTV 480p/i); 800 x 600 (SVGA); 832 x 624 (MAC 16")
Frequency	Horizontal: 15-100 kHz (RGB: 24 kHz- 100 kHz); Vertical: 50 - 120 Hz			

Connectivity

RGB (analog)	Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin
Digital	Input: 2 x HDMI™ (Deep Color, Lip sync)
Video	Input: 1 x RCA
Audio	Input: 2 x 3.5 mm Stereo Mini Jack; 2 x RCA Stereo Output: 1 x 3.5 mm Stereo Mini Jack (variable)

Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN	1 x RJ45; Optional WLAN
USB	1 x Type A (USB 2.0 high speed); 1 x Type B
Video Signals	NTSC; PAL; PAL60; SECAM

Remote Control

Remote Control	Aspect Ratio; Audio Control; Auto Adjust; AV Mute; Digital Zoom; Freeze; Help Eco Mode; ID set; Optional Presentation and Mouse Control; Picture Adjust; Picture Mode; Source Select
----------------	--

Electrical

Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	230 (Normal) / 193 (Eco) / 2.3 (Network Stand-by) / 0.45 (Stand-by); 297 (High Bright)

Mechanical

Dimensions (W x H x D) [mm]	339 x 108.5 x 259 (without lens and feet)
Weight [kg]	2.9
Fan Noise [dB (A)]	29 / 36 (Eco / Normal)

Environmental Conditions

Operating Temperature [°C]	5 to 40
Operating Humidity [%]	20 to 80
Storage Temperature [°C]	-10 to 50
Storage Humidity [%]	20 to 80

Ergonomics

Safety and Ergonomics	CE; EAC; ErP; RoHS; TUEV Type Approved; WEEE
Speakers [W]	1 x 20 (mono)

Additional Features

Special Characteristics	Auto Eco Mode; Auto Power ON/OFF; Carbon Savings Meter; Colour Management; Content Transmission via Network; Crestron RoomView; DICOM simulation; Direct Power-Off Function; High Altitude Mode; Kensington security slot; Keypad Lock; Keystone Correction (H=±30°, V=±30°); Lens Cover; Magnify; NaViSet Administrator 2; Off-Timer; Optional User Logo; Optional WLAN; OSD with 29 languages; Password Security System; Quick On/Off; RS-232 Control; Security Bar; USB Display; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction
-------------------------	---

Green Features

Energy Efficiency	75 % AV mute function; Auto ECO Mode; ECO scheduler; Green one touch ECO and AV mute button; Intelligent Power Management; Longer Light Source Life; Reduced power consumption. Only 0.45W stand-by; Software scheduling
Ecological Materials	100% recyclable packaging; Downloadable manuals; ECO packaging
Ecological Standards	ErP compliant; RoHS compliant; WEEE

Warranty

Projectors	3 years pan-European service
Light Source	6 months, max. 1000 hrs

Shipping Content

Shipping Contents	IR Remote Control (RD-469E); Mini D-SUB Signal Cable (1.8 m); Quick Setup Guide; Security Sticker; Users Manual on CD-ROM; Utility software
-------------------	---

Optional Accessories

Optional Accessories	DisplayNote; Lamp (NP43LP, NP16LP); MultiPresenter Stick; Wireless LAN module NP05LM2 (Europe), NP05LM4 (Russia)
----------------------	--

¹ Compliance with ISO21118-2012



TUEV Type Approved



CE



ErP



RoHS