

## NEC ME401X

Professional Business Projector

# Datasheet



### Great performance with low TCO.

Guaranteeing the perfect support for successful lectures and presentations, the compact multi-purpose ME401X projector delivers crisp images and natural colours to your classroom and meeting facility thanks to LCD technology and 4000 ANSI lumen brightness. Comprehensive connectivity and optional WiFi provide the utmost flexibility and time saving operation. The pre-installed MultiPresenter function enables simultaneous wireless presenting and sharing for up to 16 devices when the optional WiFi is chosen. Extended lamp and filter life are lowering both maintenance time and cost ensuring a smooth operation over 5 years\*.

The ME401X is the perfect choice when considering replacing M Series XGA LCD projectors. With the same footprint, lens position and throw angle it has never been easier to bring the latest technology to your classroom or meeting facility saving both time and money with no maintenance. With its downward compatibility for lamps of the M LCD series, even your stock is a safe investment!

\*at 8 hours operation a day, 200 days a year

### Benefits

**Large 1.7x optical zoom** – for maximum flexibility.

**Minimized cost of ownership** – due to long lamp life and filter exchange intervals.

**Versatile and mobile** – compact and light-weight with HDMI and integrated 20W speaker.

**Display content that demands attention** – with XGA resolution and superb brightness levels and colour ranges, your viewers will enjoy an outstanding visual experience.

**Cost effective replacement** – of existing NEC M LCD model installations to achieve better imaging for lectures and presentations without wall-mount adjustment.

## Product Information

Product Name	NEC ME401X
Product Group	Professional Business Projector
Order Code	60004250

## Image

Projection Technology	3LCD Technology			
Native Resolution	1024 x 768 (XGA)			
Aspect Ratio	4:3			
Contrast Ratio <sup>1</sup>	12000:1			
Brightness <sup>1</sup>	4000 ANSI Lumen			
Lamp	240 W AC (140 W AC Eco Mode)			
Light Source Life [hrs]	5000 (9000 Eco Mode)			
Lens	F= 1.7-2.1, f= 17.5-29 mm			
Keystone correction	+/- 30° manual horizontal / +/- 30° manual vertical			
Projection Factor	1.3 - 2.2 : 1			
Projection Distance [m]	0.6 - 13.8			
Screen Size (diagonal) [cm] / [inch]	Maximum: 762 / 300"; Minimum: 76 / 30"			
Zoom	Manual			
Focus Adjustment	Manual			
Supported Resolutions	1024 x 768 (MAC 19"); 1024 x 768 (XGA); 1152 x 870 (MAC 21"); 1280 x 1024 (MAC 23"); 1280 x 1024 (SXGA); 1280 x 720 (HDTV 720p);	1280 x 768 (WXGA); 1280 x 800 (WXGA); 1400 x 1050 (SXGA+); 1440 x 900 (WXGA+); 1600 x 1200 (UXGA); 1600 x 900 (WXGA++);	1680 x 1050 (WSXGA+); 1920 x 1080 (HDTV 1080p/i); 1920 x 1200 (WUXGA); 640 x 480 (MAC 13"); 640 x 480 (VGA); 720 x 480 (480p);	720 x 480 (SDTV 480i); 720 x 576 (SDTV 480p/i); 800 x 600 (SVGA); 832 x 624 (MAC 16")
Frequency	Horizontal: 15-100 kHz (RGB: 24 kHz- 100 kHz); Vertical: 50 - 120 Hz			

## Connectivity

RGB (analog)	Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin
Digital	Input: 2 x HDMI™ (Deep Color, Lip sync)
Video	Input: 1 x RCA
Audio	Input: 2 x 3.5 mm Stereo Mini Jack; 2 x RCA Stereo Output: 1 x 3.5 mm Stereo Mini Jack (variable)

Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN	1 x RJ45; Optional WLAN
USB	1 x Type A (USB 2.0 high speed); 1 x Type B
Video Signals	NTSC; PAL; PAL60; SECAM

## Remote Control

Remote Control	Aspect Ratio; Audio Control; Auto Adjust; AV Mute; Digital Zoom; Freeze; Help Eco Mode; ID set; Optional Presentation and Mouse Control; Picture Adjust; Picture Mode; Source Select
----------------	--

## Electrical

Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	230 (Normal) / 193 (Eco) / 2.3 (Network Stand-by) / 0.45 (Stand-by); 304 (High Bright)

## Mechanical

Dimensions (W x H x D) [mm]	339 x 108.5 x 259 (without lens and feet)
Weight [kg]	2.9
Fan Noise [dB (A)]	29 / 37 (Eco / Normal)

## Environmental Conditions

Operating Temperature [°C]	5 to 40
Operating Humidity [%]	20 to 80
Storage Temperature [°C]	-10 to 50
Storage Humidity [%]	20 to 80

## Ergonomics

Safety and Ergonomics	CE; EAC; ErP; RoHS; TUEV Type Approved; WEEE
Speakers [W]	1 x 20 (mono)

## Additional Features

Special Characteristics	Auto Eco Mode; Auto Power ON/OFF; Carbon Savings Meter; Colour Management; Content Transmission via Network; Crestron RoomView; DICOM simulation; Direct Power-Off Function; High Altitude Mode; Kensington security slot; Keypad Lock; Keystone Correction (H=±30°, V=±30°); Lens Cover; Magnify; NaViSet Administrator 2; Off-Timer; Optional User Logo; Optional WLAN; OSD with 29 languages; Password Security System; Quick On/Off; RS-232 Control; Security Bar; USB Display; USB Viewer for JPEG; Virtual Remote for direct PC control; Wall Colour Correction
-------------------------	---

### Green Features

Energy Efficiency	75 % AV mute function; Auto ECO Mode; ECO scheduler; Green one touch ECO and AV mute button; Intelligent Power Management; Longer Light Source Life; Reduced power consumption. Only 0.45W stand-by; Software scheduling
Ecological Materials	100% recyclable packaging; Downloadable manuals; ECO packaging
Ecological Standards	ErP compliant; RoHs compliant; WEEE

### Warranty

Projectors	3 years pan-European service
Light Source	6 months, max. 1000 hrs

### Shipping Content

Shipping Contents	IR Remote Control (RD-469E); Mini D-SUB Signal Cable (1.8 m); Quick Setup Guide; Security Sticker; Users Manual on CD-ROM; Utility software
-------------------	---

### Optional Accessories

Optional Accessories	DisplayNote; Lamp (NP43LP, NP16LP); MultiPresenter Stick; Wireless LAN module NP05LM2 (Europe), NP05LM4 (Russia)
----------------------	--

<sup>1</sup> Compliance with ISO21118-2012



TUEV Type Approved



CE



RoHS



ErP