

Datasheet



Visible yet noiseless - bringing a sense of calm to your meeting spaces

Scalable visualisation has never been so silent. With an outstandingly low noise level of just 22dB*, the P525WL is quieter than the ticking of a watch.

Thanks to the completely sealed engine, this laser projector is filter-free meaning 20,000 hours of maintenance-free operation. Comprehensive connectivity and optional WiFi provide the utmost flexibility and time saving operation. The enhanced embedded MultiPresenter functionality enables wireless presentation and screen sharing for up to 16 devices simultaneously, out of the box to your meeting room. The technology is future-proof with the capability of processing 4K inputs at 30Hz. Bringing the future of projection to your meeting room has never been easier, quieter and as low maintenance than with the NEC P525WL.

*in Eco mode / Normal mode: 24 dB / High Bright mode: 27 dB

Benefits

No filter service required - a completely sealed optical laser LCD engine allows a filter-free design. Brilliant colour brightness is maintained and servicing costs need no longer feature in your budget.

Low Noise Level - with 22dB*, the silent technology will not disturb your meeting.

Future-proof input management - thanks to 4K@30 Hz input processing.

No lamp replacement - up to 20,000 h maintenance free operation possible due to Laser Light Source.

Risk Group 2 - because of the Risk Group 2 compliance, no prescribed safety precautions are necessary.

Product Information

Product Name	NEC P525WL
Product Group	Laser Projector
Order Code	60004328

Image

Projection Technology	3LCD Technology
Native Resolution	1280 x 800 (WXGA)
Aspect Ratio	16:10
Contrast Ratio ¹	500000:1
Brightness ¹	5000 ANSI Lumen (approx. 60% in Eco Mode)
Lamp	Laser Light Source
Light Source Life [hrs]	20000 ²
Lens	F= 1.5-2.1, f= 17.2-27.6 mm
Lens shift	H:±29, V:+60,-0
Keystone correction	+/- 30° manual horizontal / +/- 30° manual vertical
Projection Factor	1.23 - 2 : 1
Projection Distance [m]	0.8 - 13.5
Screen Size (diagonal) [cm] / [inch]	Maximum: 762 / 300"; Minimum: 76.2 / 30"
Zoom	Manual; x1.6
Focus Adjustment	Manual
Supported Resolutions	3840 x 2160 (Maximum resolution of digital input); 3840x2160 @ 30hz digital; 1280x800 (Maximum resolution of analog input)

Connectivity

RGB (analog)	Input: 1 x Mini D-sub 15 pin
Digital	Input: 1 x HDBaseT; 2 x HDMI™ supporting HDCP
Audio	Input: 1 x 3.5 mm Stereo Mini Jack for Computer analog; 2 x HDMI audio Output: 1 x 3.5 mm Stereo Mini Jack (variable)
Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN	1 x RJ45; Optional WLAN
USB	1 x Type B (for Service); 1x Type A (USB 2.0 high speed) with 2.0A Power Supply; 1x Type A (W-LAN Dongle)
Video Signals	NTSC 3.58; NTSC 4.43; PAL; PAL-M; PAL-N; PAL60; SECAM

Remote Control

Remote Control	Aspect Ratio; Audio Control; Auto Adjust; Eco Mode Control; Freeze-function; Help-function; ID set; Keystone Correction; Magnify-function; Page (up, down); Picture Adjust; Picture Mute; Power (On-OFF); Presentation and Mouse Control; Select (up, down, left, right); Source Select
----------------	---

Electrical

Power Supply	100-240 V AC; 50 - 60 Hz
Power Consumption [W]	320 (Normal) / 238 (Eco) / 1.6 (Network Stand-by) / 0.3 (Stand-by)

Mechanical

Dimensions (W x H x D) [mm]	480 x 122 x 407 (without lens and feet)
Weight [kg]	9.7
Fan Noise [dB (A)]	22 / 24 / 27 (ECO / Normal / High Bright)

Environmental Conditions

Operating Temperature [°C]	5 to 40
Operating Humidity [%]	20 to 80
Storage Temperature [°C]	-10 to 50
Storage Humidity [%]	20 to 80

Ergonomics

Safety and Ergonomics	CE; EAC; ErP; RoHS; TUEV Type Approved; TÜV GS
Speakers [W]	1 x 20 (mono)

Additional Features

Special Characteristics	Auto Power ON/OFF; Carbon Savings Meter; Constant Brightness Mode; Control ID Function; DICOM simulation; Direct Power-Off Function; Free Tilt; HDBaseT; Help Function; HTTP Browser Control; Kensington security slot; Keypad Lock; Light Source Adjustment; Magnify; Mouse Control with USB Display; MultiPresenter Function; NaViSet Administrator 2; Optional User Logo; OSD with 30 languages; Password Security System; Plug&Play W-LAN Option; Portrait Setting; Quick Start; Source Select with Beep Function; Test Pattern; Unique Power Saving Functions; USB Viewer; Virtual Remote for direct PC control
-------------------------	--

Green Features

Ecological Materials	Downloadable manuals; ECO packaging
Ecological Standards	ErP compliant; RoHs compliant

Warranty

Projectors	3 years pan-European service
Light Source	3 years or 10000h (whatever comes first)

Shipping Content

Shipping Contents	2x AAA Batteries; IR Remote Control (477E); Mini D-SUB Signal Cable (1.8 m); Power Cord (1.8 m); Projector; Quick Setup Guide; Security Sticker; Users Manual; Utility software
-------------------	---

Optional Accessories

Optional Accessories	Universal Ceiling Mounts (PJ01UCM, PJ02UCMPF); Wireless LAN module (NP05LM2; NP05LM4; NP05LM5)
----------------------	--

¹ Compliance with ISO21118-2012

² 50% of initial brightness at the end of specified laser life time at 25 degree ambient temperature.



TÜV GS

TUEV Type
Approved

CE



ErP



RoHS

This product has been equipped with a laser module and is classified as Class1 of IEC60825-1 Ed3 2014 and is classified as RG2 of IEC62471-5 Ed1 2015.

DO NOT LOOK DIRECTLY INTO THE BEAM.

This document is © 2021 Sharp NEC Display Solutions Europe GmbH.

All rights reserved in favour of their respective owners. All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All specifications are subject to change without notice. Errors and omissions are excepted. 27.11.2021