

NEC MultiSync® LCD1970NXp





NEC Display Solutions

• Ergonomics and safety complying to the highest industry standards incl. ISO 13406-2

- Safety of investment with analog/digital interface
- ErgoDesign®: Height adjustable stand (110 mm) with 90° Pivot features
- Versatile and easy installation (VESA standard) with NaViSet and NaViKey
- Stable and excellent picture quality with NTAA (Non-Touch-Auto-Adjustment) and PVA TFT display

Fully featured office monitors with outstanding display quality and ergonomic performance.

NEC MultiSync® LCD1970NXp

TECHNICAL SPECIFICATIONS	
Panel Technology	PVA TFT
Screen Size [inch/cm]	19 / 48.2
Pixel Pitch [mm]	0.294
Viewing Angle [°]	176 horizontal / 176 vertical (typ. at contrast ratio 10:1)
	176 horizontal / 176 vertical (typ. at contrast ratio 5:1)
Contrast Ratio (typ.)	1500:1
Brightness (typ.) [cd/m²]	250
Response Time (typ.) [ms]	20 (11 white / black; 9 black / white)
Colours [Mio.]	16.77
Horizontal Frequency [kHz]	31.5 - 81.1
Vertical Frequency [Hz]	56 - 75
Optimum Resolution	1280 x 1024 at 60 Hz
Supported Resolutions	1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480
Connectors	Digital: 1 x DVI-D; Analog: 1 x mini D-sub 15 pin
Plug & Play	VESA DDC/CI; DDC2B/2Bi; EDID Standard
Adjust Functions	Auto Adjust; Brightness; Colour Temperature Control; Contrast; Fine Adjust (analog); Intelligent Power
	Management; Language Select; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-
	Screen-Display (OSD) lock-out; sRGB
Safety and Ergonomics	CE; TCO 03; TÜV Ergonomics; TÜV GS; GEEA/Energy Label; Energy Star; FCC Class B; PCT/Gost; UL/
	C-UL or CSA; CCC; ISO 13406-2 (pixel failure class II); MPR II/ MPR III; RoHS
Power Consumption on Mode [W]	38 (typ.)
Power Consumption Power-Saving Mode [W]	< 2
Power Supply	100-120 V/220-240 V; 1.2 A/0.6 A; internal power supply
Ambient Temperature (operating) [°C]	+5 to +35
Ambient Humidity (operating) [%]	30 to 80
VESA Mounting [mm]	100 x 100
ErgoDesign®: Height adjustable Stand [mm]	110
Screen Tilt / Swivel / Rotate [°]	-5 to +30 / -170 to +170 / 0 to 90 (landscape to portrait mode)
Dimensions (W x H x D) [mm]	412.5 x 386.5 x 230.0
Bezel Width [mm]	17.1
Weight [kg]	8.0
Cable Management	yes
Kensington Lock	yes
Benefits	NaViSet® and NaViSet® Administrator compatible; Rapid Response Technology; sRGB Support;
	TORO™ Design
Audio Functions	Option: MultiSync® Soundbar 70
Colour Versions	Silver Front Bezel, Black Back Cabinet
	Silver Front Bezel, Light Grey Back Cabinet
Shipping Content	Monitor; Power Cable; Signal Cable VGA - VGA; CD-ROM; Sales Office List; User Manual
Warranty	3 years warranty incl. backlight



4

All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. 09/08

www.nec-display-solutions.co.uk

NEC Display Solutions UK Ltd, 32 Southwark Bridge Road, London SE1 9EU Phone: 0207 202 6300, e-mail: infomail@nec-displays.com For further information on NEC products call: 08701 201160