

NEC MultiSync® LCD1770NX





Fully featured office monitors with outstanding display quality and ergonomic performance.

- Ergonomics and safety complying to the highest industry standards incl. ISO 13406-2
- ErgoDesign®: Height adjustable stand (110 mm)
- Safety of investment with analog/digital interface
- Versatile and easy installation (VESA standard) with NaViSet and NaViKey
- Stable and excellent picture quality with NTAA (Non-Touch-Auto-Adjustment)

NEC MultiSync® LCD1770NX

TN+ film TFT
17 / 43
0.264
178 horizontal / 178 vertical (typ. at contrast ratio 5:1)
160 horizontal / 160 vertical (typ. at contrast ratio 10:1)
800:1
300 (LCD Module at 25 °C)
5 (1 white / black; 4 black / white)
16.7
31.5 - 81.0
56 - 75
1280 x 1024 at 60 Hz
1152 x 870; 1152 x 864; 1024 x 768; 832 x 624; 800 x 600; 720 x 400; 640 x 480
Digital: 1 x DVI-D; Analog: 1 x mini D-sub 15 pin
VESA DDC/CI; EDID Standard; VESA DDC2B
Auto Adjust; Brightness; Colour Temperature Control; Contrast; Fine Adjust (analog); Intelligent Power
Management; Language Select; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-
Screen-Display (OSD) lock-out; sRGB
CE; ERP; TCO 03; TÜV Ergonomics; TÜV GS; GEEA/Energy Label; FCC Class B; PCT/Gost; UL/C-UL or
CSA; CCC; ISO 13406-2 (pixel failure class II); MPR II/ MPR III; RoHS
36 (typ.)
<2
100-120 V/220-240 V; 0.7 A/0.35 A; internal power supply
+5 to +35
10 to 80
100 x 100
110
-5 to +30 / -170 to +170
367 x 362.5 x 198
13.6
6.1
ves
ves
NaViSet®and NaViSet®Administrator compatible; Rapid Response Technology; sRGB Support
Option: MultiSync® Soundbar 70
Silver Front Bezel, Black Back Cabinet
Silver Front Bezel, Light Grey Back Cabinet
Monitor; Power Cable; Signal Cable VGA - VGA; CD-ROM; Sales Office List; User Manual
3 years warranty incl. backlight

























All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. 03/1